

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION AND USES

Product Name	ULTRA WASH (CH 600)	CI#	Not
Synonyms	Not available.	applicable.	
Chemical Name	Not applicable.	DSL	Not
Chemical Formula	Chemical mixture.	available.	
Chemical Family	Alcohol/aliphatic hydrocarbon blend.	CAS#	Not
Supplier	DEK Canada Inc. 1928 St. Regis Blvd., Dorval, Quebec H9P 1H6 Phone: (514) 685-5800		
Material Uses	Electronic Equipment Cleaner		

SECTION 2: HAZARDOUS INGREDIENTS

Name	Cas#	% by Weight	LC ₅₀ /LD ₅₀
1) Ethanol	64-17-5	10-30	ORAL (LD50) mg/kg: Acute: 7060 (Rat). Dermal (LD50) mg/kg: Acute: 20000 (Rabbit). Vapor (LC50) ppm: Acute: 8000 (Rat.) (4 hour (s)).
2) Isopropyl Alcohol	67-63-0	3-7	Oral (LD50) mg/kg: Acute: 3600 (Mouse). 5045 (Rat). Vapor (LC50) ppm: Acute: 22600 (Rat) (4 hour(s)).
3) N-hexane	110-54-3	40-80	ORAL (LD50) mg/kg: Acute: 32400 (Rat).
4) Ethyl acetate	141-78-6	1-5	ORAL (LD50) mg/kg: Acute: 5620 (Rat). 4100 (Mouse). 4935 (Rabbit).
5) Carbon dioxide	124-38-9	1-5	Not available.

SECTION 3: PHYSICAL DATA

Physical State and Appearance	Liquid (Aerosol Concentrate).	Odor	Mild.
pH (1% Soln/Water)	Not available.	Taste	Not available.
Odor Threshold	50 ppm based on data for: Isopropyl alcohol Weighted average: 40 ppm	Color	Clear, colourless.
Volatility	Not available.		
Evaporation Rate	Not available.		
Melting Point	Not available.		
Boiling Point	The lowest known value 149°F (N-hexane).		
Density	0.695 – 0.705 (Water = 1)		
Vapor Density	Greater than 1 (Air = 1)		
Vapor Pressure	Not available.		
LogK_{ow}	Not available.		
Ionicity (Surface Active Agent)	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Conditions of instability	Not additional remark.		
Dispersion Properties	See solubility in water.		
Solubility	Miscible in water.		

Continued on Next Page

SECTION 4: FIRE AND EXPLOSION DATA

The Product is:	Extremely Flammable Aerosol.
Auto-ignition Temperature	The lowest known value 433.4 ^o F (N-hexane).
Products of Combustion	These products are carbon oxides (CO, CO2) and other irritating gases.
Flash Points	The lowest known value CLOSED CUP: -16.6 ^o F (Tagliabue) (N-hexane).
Flammable Limits	LOWER: 0.6% UPPER: 19%.
Extinguishing Media	SMALL FIRE: Use DRY chemicals, CO2 or foam. LARGE FIRE: Use foam or water fog. Cool containing vessels with water spray in order to prevent pressure build-up, auto-ignition or explosion. Avoid spreading burning liquid with water used to cool containers. Self-contained respiratory protection should be provided for firefighters.
Flammability	The flammability of an aerosol by WHMIS definition is determined by its flame-extension of this product is greater than 45 cm. Canadian NFC, Level 3 Aerosol. Do not use in the presence of open flame or spark. Do not place in hot water or near radiators, stoves or other sources of heat.
Risks of Explosion	Risks of explosion of the product in presence of mechanical impact: Do Not subject aerosol cans to impact. Risks of explosion of the product in presence of static discharge: Vapours of this product may form a flammable/explosive mixture with air in enclosed areas when vapours present are between the lower (0.6%) and upper (19%) flammable limits and come into contact with open flames , sparks or static discharge. DO NOT expose aerosol containers to open flames, heat or ignition sources. Container may explode if heated.

SECTION 5: REACTIVITY

Stability	The product is stable.
Hazardous decomposition Products	These products are carbon oxides (CO, CO2) and other irritating gases.
Degradability	Not available.
Products of Degradation	Not available.
Corrosivity	Not considered to be corrosive for metals and glass according to our database.
Reactivity	Avoid contact with strong oxidizing agents, strong acids and strong alkalies
Instability Temperature	Not available.
Conditions of Instability	No additional remark.

SECTION 6: TOXICOLOGICAL PROPERTIES

Routes of Entry	Ingestion. Inhalation. Skin contact. Eye contact.
TLV	Ethanol TWA: 1000 (ppm) from ACGIH Isopropyl alcohol TWA: 400 CEIL: 500 (ppm) TWA: 980 CEIL: 1225 (mg/m ³) N-hexane TWA: 50 CEIL: 125 (ppm) TWA: 360 CEIL: 450 (mg/m ³) Ethyl acetate TWA: 400 (ppm) TWA: 1400 (mg/m ³) Carbon dioxide TWA: 5000 (ppm) Consult local authorities for acceptable exposure limits.

Continued on Next Page

Toxicity to Animals	WARNING: THE CL50 VALUE HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50):> 5000 mg/kg (Rat) (Ethanol). Acute oral toxicity (LD50): 3600 mg/kg (Mouse) (Isopropyl alcohol). Acute oral toxicity (LD50):> 5000 mg/kg (Rat) (N-hexane). Acute oral toxicity (LD50): 4100 mg/kg (Mouse) (Ethyl acetate). Acute toxicity of the vapor (LC50):> 5000 ppm (Rat.) (Ethanol). Acute toxicity of the vapor (LC50):> 5000 ppm (Rat.) (Isopropyl alcohol).
Chronic Effects on Humans	Prolonged or repeated skin contact may lead to dermatitis.
Acute Effects on Humans	EYE CONTACT: May cause severe irritation, redness, tearing and blurred vision. SKIN CONTACT: May cause irritation, defatting, drying and cracking of skin. INHALATION: Vapours may be irritating to nose, throat and respiratory tract. Excessive inhalation of vapours may cause Central Nervous System Effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. INGESTION: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Can be fatal if inhaled or ingested.
Synergetic Products (Toxicologically)	Not available.
Irritation/Corrosivity	Not available.
Sensitization	Not available.
Carcinogenic Effects	Not available.
Toxic Effects on Reproduction	Not available.
Teratogenic Effects	Not available.
Mutagenic Effects	Not available.

SECTION 7: PREVENTIVE MEASURES

Small Spill and Leak	Ventilate area and eliminate all sources of ignition. Keep away from heat. Soak up with an absorbent material. It is recommended that chemical resistant gloves and safety glasses be worn to clean up spills.
Personal Protective Equipment	It is recommended to wear safety glasses and chemical resistant gloves.
Large Spill and Leak	Not applicable for aerosol containers.
Protective Clothing	Not applicable for aerosol containers.
Engineering Controls	Use under well-ventilated conditions.
Precautions	Contents under pressure. Container may explode if heated. Direct inhalation of spray may be harmful. Keep out of reach of children.
Storage	Store in a cool, dry place. Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 50°C or in direct sunlight.
Handling	Do not use in the presence of open flame, sparks or ignition sources. Keep away from Heat. Avoid breathing vapours or spray mists. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. After handling, always wash hands thoroughly with soap and water.
Waste Disposal	Recycle to process, if possible. Consult your local or regional authorities. Do not dispose in sewers. When container is empty, press button to release all pressure, then dispose of in garbage can.
Special Shipping Information	None.

Continued on Next Page

SECTION 8: FIRST AID

Eye Contact	Flush eyes with plenty of water for 15 minutes, lifting upper and lower lids, occasionally. Contact physician.
Skin Contact	Wash thoroughly with soap and water. If irritation occurs or persists, get medical attention. Remove contaminated clothing and wash before reuse.
Slight Inhalation	Remove affected person to fresh air. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Contact medical center or physician immediately.
Hazardous Inhalation	No additional information.
Slight Ingestion	If swallowed, call physician or poison control center immediately. Do not induce vomiting. Aspiration of material into lungs due to vomiting may cause chemical pneumonitis which can be fatal.
Hazardous Ingestion	No additional information.

SECTION 9: MSDS PREPARATION

References	Not available.
No additional remark.	
Validated by DEK Canada Inc. on Feb. 27/09 Tel 514-685-5800	Verified by DEK Canada Inc. Printed Feb. 27/09
Emergency Phone: Please contact the local authorities.	

CLASSIFICATION

TDG Road/	CONSUMER COMMODITY. Not applicable.
WHMIS	WHMIS CLASS A: Compressed gas. WHMIS CLASS B-5: Flammable aerosol. WHMIS CLASS D-2B: Material causing other toxic effects (TOXIC).
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination or suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.	