

DOMINO

GARAGE DOOR KEYPAD

Model GD-1



DESCRIPTION

The *DOMINO GARAGE DOOR KEYPAD* is a simple and convenient way to open and close garage doors. Consisting of an outside mounted keypad and inside control box, the *DOMINO GARAGE DOOR KEYPAD* features personalized code setting, making the system as easy to program as it is to install.

FEATURES

- Universal Use
Compatible with all garage door openers.
- Easy Programming
Keypad is quickly programmed in three simple steps.
- Code Security
Keypad shuts off for one minute after five wrong entries have been pressed.
- Protective Cover
Flip-Up cover design protects the unit against the elements.
- Personalized User Code
A 1 through 6 digit code may be chosen, over 1,000,000 possibilities.
- Back Lighting
Lighted keypad for easy nighttime operation. Additional indicator light provides verification as keys are pressed.
- Low Power Warning / Battery Saver
Lights dim to indicate batteries should be replaced soon. Special sleep circuitry conserves battery life.
- Instant Stop
After code is entered and garage door opener is activated, the "enter" key may be pressed again to stop or reverse the door, without re-entering the code. The "enter" key remains active for 20 seconds.
- Additional Push Button
Conveniently located on control box.

BENEFITS



DOMINO ENGINEERING CORPORATION

P.O. Box 376 • Taylorville, IL 62568 • www.dominoengineering.com
1-800-7DOMINO (1-800-736-6466) • 217-824-9441 • Fax (217) 824-3349
E-mail: info@dominoengineering.com

DOMINO

GARAGE DOOR KEYPAD

Model GD-1

SPECIFICATIONS

Outside Keypad Size:

Length 5" (12.5cm); Width 2" (5cm); Depth .6" (1.5cm)

Inside Control Box Size:

Length 3" (7.5cm); Width 4.5" (11.5cm); Depth 1.4" (3.5cm)

Materials:

ABS plastic; Rubber keypad

Electrical Input:

3 AA alkaline batteries

Electrical Output:

1 amp dry contact relay

.3 - 3.5 second activation



The *DOMINO GARAGE DOOR KEYPAD* Self-selling color package includes Domino keypad, control box, three AA batteries, screws, installation instructions and sticker with 1-800 help line number.

INSTALLATION

Keypad:

Two concealed 3/4" screws. Outside keypad is wired to inside control box with modular telephone cable and connector.

Control Box:

Two 3/4" screws. Two low voltage wires required to connect from control box to wall push button or terminals on opener.

PROGRAMMING

1. At control box, slide program switch "Program."
2. At keypad, press "Enter," "your code" (up to six digits), and "Enter."
3. At control box, slide program switch to 'Operate.'

additional products

DOMINO

- Entry door keypad
- Wireless garage door alarm
- GD-1 sales demonstrator
- Radio control adapter for commercial doors
- Safety reverse converter for commercial doors

DOMINO GARAGE DOOR KEYPAD - One Year Warranty

Domino Engineering Corporation will repair or replace at its discretion, any *DOMINO GARAGE DOOR KEYPAD* failing to operate properly for any reason (except vandalism or abusive use), within a period of 12 months from date of purchase. Send failed unit and \$5.00 for shipping and handling to: Domino Engineering Corporation, 208 S. Spresser, P.O. Box 376, Taylorville, IL 62568-0376.

Extended Warranty

Domino Engineering Corporation will repair or replace at its discretion, any *DOMINO GARAGE DOOR KEYPAD* failing to operate properly for any reason (except vandalism or abusive use), within a period of 5 years from date of purchase. Send failed unit and \$15.00 plus \$5.00 for shipping and handling to: Domino Engineering Corporation, 208 S. Spresser, P.O. Box 376, Taylorville, IL 62568-0376. A new or repaired unit will be shipped.



DOMINO ENGINEERING CORPORATION

P.O. Box 376 • Taylorville, IL 62568 • www.dominoengineering.com
1-800-7DOMINO (1-800-736-6466) • 217-824-9441 • Fax (217) 824-3349
E-mail: info@dominoengineering.com