

Introducing the LiftMaster® KPW250 and KPW5
The Best Wireless Keypads. Period.



SLEEK WIRELESS DESIGN. SIMPLE INSTALLATION. RELIABLE PERFORMANCE.

Built to deliver unbeatable performance in tough environments, LiftMaster® Wireless Keypads enable a more modern, streamlined access solution that's simpler than ever to install and use.

ADVANTAGES YOU WON'T FIND ANYWHERE ELSE.

Only LiftMaster Wireless Keypads:

- Come equipped with Security+ 2.0® to offer maximum range and virtually eliminate interference
- Electronics are fully sealed and meet NEMA 4X water protection requirements
- Offer the most temporary PINs—10 unique temporary PINs that can be set for 1 to 9 uses

KPW250

The best features of any wireless keypad on the market.



Ideal for larger
commercial
applications.



- Programs to all LiftMaster Gate and Commercial Door Operators
- Enables flexible setup for multiple users with 250 permanent PINs and 10 unique temporary PINs
 - Allows for removal of a single PIN while maintaining full access for other users
- Compatible with Security+ 2.0, Security+® and Linear Multi-Code* 300 MHz
- Withstands harsh environments with a zinc-alloy metal front cover



KPW5

Ideal for residential gate access, including solar gate applications, as well as smaller commercial door and gate applications.



- Designed to work exclusively with Security+ 2.0®
- Enables flexible setup with 5 permanent PINs and 10 unique temporary PINs
 - Allows for removal of a single PIN while maintaining full access for other users
- Enclosed in a high-impact polycarbonate front cover that stands up to the elements

OPTIONAL ACCESSORIES



Gooseneck Pedestal (PED42)

- 42 in. pad-mount pedestal
- 2 x 2 in. square pipe
- Black powder-coated finish
- 11 ga. steel



Gooseneck Pedestal (PED64)

- 64 in. in-ground mount pedestal
- 2 x 2 in. square pipe
- Black powder-coated finish
- 11 ga. steel



Universal Receiver (850LM)

- Security+ 2.0 Technology
- 3 channels for expanded capacity
- Stores up to 90 remote controls
- Compatible with most gate and commercial door operators

TECHNOLOGY OVERVIEW AND SPECIFICATIONS

| MODEL | CODE AND RADIO FREQUENCY OPTIONS | PIN CAPACITY |
|--------|--|---|
| KPW250 | <ul style="list-style-type: none"> LiftMaster® Security+ 2.0® (Default) <ul style="list-style-type: none"> – Delivered on Tri-Band 310/315/390 MHz LiftMaster Security+® 315 MHz LiftMaster Security+ 390 MHz Linear Multi-Code® 300 MHz | <ul style="list-style-type: none"> Up to 250 Permanent Four-Digit PINs Up to 10 Unique Temporary PINs |
| KPW5 | <ul style="list-style-type: none"> LiftMaster Security+ 2.0 <ul style="list-style-type: none"> – Delivered on Tri-Band 310/315/390 MHz | <ul style="list-style-type: none"> Up to 5 Permanent Four-Digit PINs Up to 10 Unique Temporary PINs |

| SYSTEM FEATURES | SPECIFICATIONS |
|--|--|
| Operating Voltage | 9V Lithium Battery with Battery Life Up to Five Years (Based on 25 Activations per Day) |
| Operating Temperature | –4°F to 140°F (–20°C to 60°C) |
| Storage and Shipping Temperature Range | –40°F to 140°F (–40°C to 60°C) |
| Operating Humidity | 5% to 95% (Non-Condensing) |
| Weatherization | Electronics Meet NEMA 4X Water Protection Requirements Housing Meets or Exceeds NEMA 3R |
| Enclosure | KPW250: Zinc-Alloy Metal Front Cover; High-Impact Polycarbonate Back Housing KPW5: High-Impact Polycarbonate Front Cover and Back Housing |
| Warranty | One Year Limited |
| Memory | Non-Volatile (Codes Saved When Battery Replaced) |
| Mounting | Compatible for Surface Mount or Standard Pedestal Mount (4 x 4 in.) |
| Operating Range | Up to 500 ft. (Open Field) |



KPW250 & KPW5 Dimensions: 4.3" x 6" x 1.75"
 KPW250 Weight: 1.2 lbs
 KPW5 Weight: .73 lbs



CGI IS AN ISO9001 REGISTERED COMPANY



IC/FCC
 Certified

CGI reserves the right to make design or specification changes without notice.