

SINGLE LINE TELEPHONE ACCESS CONTROL

TAC FAMILY



TAC1

SIMPLIFY YOUR LIFE WITH THE LIFTMASTER® MODEL TAC1

The LiftMaster® Model TAC1 System provides wired communication and secure access control at the gate or door. Homeowners can use any touch-tone phone in the home to speak to a visitor, and then grant or deny access through their gate or door.

Attractive and Durable

Hardwired for power and connected directly to your existing telephone line, the TAC1 greets visitors with a high-visibility backlit keypad and attractive styling. And its rugged, tamper-resistant polycarbonate enclosure is engineered for maximum impact resistance without dents or corrosion.

The Power is in your hands

The TAC1 is simple to use and allows the homeowner or small business to greet visitors, grant or deny access, or activate several system modes; all from the convenience of their touch-tone phone.



TAC2D



TAC2CK

TAC2 MODELS ARE SINGLE TENANT TELEPHONE ACCESS CONTROL

Retrofit Systems

TAC2C

The LiftMaster® Model TAC2C System provides new life to your damaged, malfunctioning, or old Crown Jewel telephone entry unit.

TAC2D

The LiftMaster® Model TAC2D System provides new life to your damaged, malfunctioning, or old 1812* telephone entry unit.

TAC2CK

Restore or replace your entire telephone access unit with TAC2CK. Kit includes back box and retrofit TAC2C.

TAC FAMILY

SECURITY. SIMPLICITY. FLEXIBILITY. WE BRING IT ALL TOGETHER.

Advanced technology means far greater simplicity. LiftMaster® security access products are easy to use, work together seamlessly and are adaptable to a variety of applications – residential and commercial.

COMMON FEATURES

Remote Open

Open 2 entrances independently from your home or office

Party Mode

To open, and hold your entrance open

Vacation Mode

Locks the system down when no administrator is present

Do Not Disturb

Silence the telephone call mode for additional privacy

Custom Caller ID

Identifies via CID display tenant call is from a Gate Visitor

Intercom Mode

Useful to make wired phones active for access in “Cellular Only” homes

Call Forward

Allows you to greet a visitor, even when you're not home

Distinctive Ringing

Provides a unique double-ring on the system's main telephone line to distinguish between a standard phone call and a visitor request call

Call Waiting

Allows a person to answer a call from the door or gate while in the middle of another outside call

Entry Codes

Up to 200 4-digit codes can be set as permanent or one-time-use only

Flexible Dual Control Feature - **TAC1 ONLY***

The TAC1 can be connected to two devices such as a door or gate, using the two independently controlled relays or wirelessly using Security+® technology standard, or any combination of the two.

Security+® Rolling Code Technology - **TAC1 ONLY***

Provides seamless wireless communication between LiftMaster door and gate openers

*TAC2 Products do not have the radio features of TAC1

ENHANCED FEATURES

Reliable 2 Stage Security Protection

Tamper Alarm

When sensors in the TAC2C detect a possible forced entry into the enclosure, the system will shut down for two minutes activating an audible alarm, and it will send a message to the phone in the home. Phones equipped with an LCD will see an alarm message.

Auto Sensor Input

May be set to automatically dial the residence when a vehicle approaches the property.

Intercom Mode

Allows use of the TAC2C with PBX systems.

SPECIFICATIONS

UL listed 12-Volt AC (20VA) Transformer Included (TAC1)

UL/CEC Listed 16-Volt DC 2.5 Amp Transformer Included (TAC2)

Alternate (10 to 16 volts AC, 20VA or 12 to 24 volts DC, 500mA)

Operating Temperature 10°F to 140°F

(2) Independently controlled (latched & timed) 10 Amp (form C) relays

(2) 315 MHz Security+® wireless channels (parallel operation to the relay)
TAC1 Only

Diagnostic and Status LEDs


On-board surge suppression

Bell REN standard: 3.0

Shipping weights:

TAC1: 4 lbs. TAC2C: 2 lbs. TAC2D: 3.5 lbs. TAC2CK: 6 lbs.

Dimensions



TAC1

TAC2C

TAC2D