CDVI

Range ERONE® Wireless Access Control Systems

MULTIUSER Multiuser Receivers

TECHNICAL FEATURES

- **Frequency :** 433,92 MHz.
- **Encoding :** Keeloq® Hopping code
- **Modulation :** ASK- FSK
- **Enclosure :** Indoor - IP30.
- **Power supply :** 12 - 24 Vac/dc
- **Memory :** 500 / 800 / 1600 Users
- **Dimensions :** 180 x 140 x 68 mm

ACCESSORIES

SEA433

> PRODUCT HIGHLIGHTS

- **Multiuser receivers for management of public parts as parkings, garages, common parts - User number from 500 to 1600 - 2 access levels: Master and User I/F RS232 for PC with sw PCCOM.**

SEL2641R433-K5: 500 users
SEL2641R433-K8: 800 users
SEL2641R433-K8P: 800 users PCCOM

SEL2641R433-K16P: 1600 users PCCOM

SEL2641F433-K5: 500 users FM

ERONE® THE SMART LIVING

WIEGAND Wiegand Receivers



> PRODUCT HIGHLIGHTS

- **Wiegand output receivers. with DATA0 and DATA1**
Open drain configuration with output signal in Wiegand 26 bit for 30 bit format.
Self learning memorization of the transmitters.

SELWR433 : Wiegand receiver

TECHNICAL FEATURES

- **Power supply :** 12 - 24 Vac/dc
- **Encoding :** Keeloq® Hopping code
- **Outputs :** 2 Open-drain
- **Enclosure :** Indoor IP2X.
- **Protocol :** Wiegand 26 - 30 bit
- **Dimensions :** 105 x 45 x 28
- **Operating temperature :** -10°C - +55°C

ACCESSORIES

SEA433

ERONE® THE SMART LIVING