CDVI

Range ERONE® - 433 MHz AM Radiocontrols

MINI Transmitter MINI AM

TECHNICAL FEATURES

- **Frequency :** 433,92 MHz.
- **Encoding :** Keeloq® Hopping code
- **Modulation :** ASK
- **Versions :** 1 - 2 Channels.
- **Battery :** 2 x CR2016 Lithium
- **Range (in open space) :** 100 - 200 m
- **Dimensions :** 60 x 36 x 16 mm

> PRODUCT HIGHLIGHTS

- **High security mini transmitter with rolling code technology, encoded in factory in encrypted and unreproducible way.**
Best use in automatic closures, public or private access, residential or industrial environment.

SETR2641AM1 : 1 ch
SETR2641AM2.B : 2 ch Blue
SETR2641AM2.C : 2 ch Dark red
SETR2641AM2.N : 2 ch Anthracite
SETR2641AM2.R : 2 ch Red

ERONE® THE SMART LIVING

Wall Transmitter WALL TX

> PRODUCT HIGHLIGHTS

- **4 channel wall fixing transmitter for awnings and sun blinds systems.**
Gummed buttons.
Elegant and suitable to any architectural context.

SETR2641-TM : 4 ch

TECHNICAL FEATURES

- **Frequency :** 433,92 MHz.
- **Encoding :** Keeloq® Hopping code
- **Modulation :** ASK
- **Versions :** 4 Channels.
- **Battery :** 2 x CR2025 Lithium
- **Range (in open space) :** 100 - 200 m
- **Dimensions :** 80 x 80 x 25 mm

ERONE® THE SMART LIVING